


Chain Grade 10 Short link, KL



Heat treatment

Quenched and tempered.
Note! For chain grade 10 the maximum in service temperature is 200°C.


Surface treatment

Painted blue

Marking

10G


Art. no. Box	Code	WLL tonnes	D nom.	L »	E »	Weight kgs/m	MPF kN	Breaking force (kN)
Z802300 - 1 x 200 m	KLA 6-10	1.5	6	18	8	0.8	37	60
Z802337 - 1 x 200 m	KLA 7-10	2.0	7	21	10	1.1	48	77
Z802301 - 1 x 200 m	KLA 8-10	2.5	8	24	11	1.4	62.5	100
Z802302 - 1 x 100 m	KLA 10-10	4.0	10	30	14	2.3	100	160
Z802303 - 1 x 100 m	KLA 13-10	6.7	13	39	18	3.8	162	260
Z802304 - 1 x 100 m	KLA 16-10	10.0	16	48	22	5.6	250	402
Z802305 - 1 x 50 m	KLA 20-10	16.0	20	60	29	9.4	393	630
Z802234 - 1 x 25 m	KLA 22-10	19.0	22	66	31	11.8	475	806
Z802235 - 1 x 50 m	KLA 26-10	27.0	26	78	37	14.6	664	1062



Master Grab MG

"All-in-one" compact top link.


Art. no.	Code	WLL tonnes*	L	A	E	D	Weight kgs
B14710	MG-6-10	1.5	145	88	60	15	0.5
B14711	MG-8-10	2.5	171	92	60	18	0.9
B14712	MG-10-10	4	211	113	75	22	1.8
B14713	MG-13-10	6.7	261	138	90	26	3.5
B14714	MG-16-10	10	311	157	105	31	6.1



Master Grab Duo MGD

"All-in-one" compact top link for 2-leg slings.


Art. no.	Code	WLL tonnes*	L	A	E	D	Weight kgs
B14700	MGD-6-10	2.1	144	90	60	17	0.7
B14701	MGD-8-10	3.5	171	100	75	21	1.3
B14702	MGD-10-10	5.6	211	124	90	24	2.3
B14703	MGD-13-10	9.5	262	149	105	31	5.2
B14704	MGD-16-10	14	310	175	120	35	7.9



Master Link MFH

Designed for crane hooks, DIN 15401 MAX. 3- and 4 leg chain slings require CLD / CGD

Art. no.	Code	WLL tonnes	For chain size, mm			L	E	D	DIN 15401	DIN 15402	Weight kgs
			1-leg	2-leg	3-4-leg						
Z101262	MFH-1310-10	7.5	13	10	8	230	125	22	≤ 12	≤ 16	1.9
Z101263	MFH-1613-10	10	16	13	10	250	135	28	≤ 12	≤ 16	3.2
Z101264	MFH-2016-10	17	20	16	13	280	135	32	≤ 16	≤ 20	4.6
Z101265	MFH-2220-10	28	-	20	16	320	175	40	≤ 25	≤ 32	8.6
Z101266	MFHW-2220-10	25	-	20	16	355	225	40	≤ 50	≤ 63	9.9



Master Link, MFX

Oversized, for 1- and 2-leg sling.

Art. no.	Code	WLL tonnes*	For chain mm, 1-leg	For chain mm, 2-leg	L	E	D	Weight kgs
Z100550	MFX-108-10	4	8, 10	8	340	180	25	3.7
Z100551	MFX-1310-10	6.7	13	10	340	180	28	4.7
Z100552	MFX-1613-10	10	16	13	340	180	34	7.1
Z101125	MFX-2016-10	16	20	16	340	180	40	8.5

Designed for use with CL, CLD, CG and CGD.