

## Midgrab Chain Shortener MIG

### Product Features

- » Instant mounting and positioning on any part of the chain.
- » Shortening in either chain direction; up or down.
- » Designed to prevent inadvertent chain disengagement.
- » Can be set idle on the chain leg when shortening is not required.
- » LC version offers secure mounting with locking set on any desired part of the chain with one chain direction open for shortening.
- » CC version offers close-open function in both chain directions for saferentention of the chain.

**Note! The MIG must be used with at least one of the locking devices.**

### Locking options for the MIG



### Locking Devices for Midgrab MIG

#### L - fixed locking set for MIG.



For fixed mounting of MIG shortener on a chain leg.

**Code:**

L-8  
L-10  
L-13

#### C - close/open locking set for MIG.



Spring operated locking device. Can be placed either in open or closed position.

**Code:**

C-8  
C-10  
C-13

Art. no.	Code	WLL tonnes*	L	X	Y	Weight kgs
B14300	MIG- 8-10	2.5	95	50	60	0.7
B14310	MIG-10-10	4.0	125	70	77	1.1
B14320	MIG-13-10	6.7	150	90	80	2.6
B14303	MIG CC-8-10	2.5	95	50	60	0.7
B14304	MIG LC-8-10	2.5	95	50	60	0.7
B14313	MIG CC-10-10	4.0	125	70	77	1.1
B14314	MIG LC-10-10	4.0	125	70	77	1.1
B14323	MIG CC-13-10	6.7	150	90	80	2.6
B14324	MIG LC-13-10	6.7	150	90	80	2.6

