


Master Link M


Art. no.	Code	WLL tonnes*	L	E	D	Weight kgs
Z101271	M-6-10	1.25	100	60	11	0.2
Z101272	M-86-10	2.5	125	70	14	0.4
Z101273	M-108-10	4	140	80	17	0.8
Z101274	M-13-10	5.4	150	90	19	1
Z101267	M-1310-10	7.5	160	95	22	1.5
Z101268	M-1613-10	10	190	110	28	2.8
Z101247	M-19-10	12	200	120	30	3.5
Z101269	M-2016-10	17	240	140	34	5.2
Z101270	M-2220-10	25	250	150	40	7.3
Z101275	M-2622-10	28	250	150	42	7.8
Z101284	M-32-10	33	300	180	45	11.7
Z101276	M-3226-10	43	300	200	50	14.8
Z101277	M-3632-10	56	350	200	55	20.7
Z101278	M-4536-10	70	375	210	60	26.4
Z101279	M-90T-10	90	450	250	70	42.8
Z101280	M-125T-10**	125	450	260	80	57

** Dimension L and E not acc. to EN 1677-4.



Master Link MF For 1-, 2-, 3- and 4-leg slings. 3- and 4 leg chain slings require CLD / CGD

Art. no.	Code	WLL tonnes*	For chain size, mm			L	E	D	Weight kgs
			1-leg	2-leg	3-4-leg				
B14487	MF-6-10	1.25	6			100	60	11	0.2
B14481	MF-86-10	2.5	6, 8	6	-	125	70	14	0.4
B14482	MF-108-10	4	10	8	6	140	80	17	0.8
B14483	MF-1310-10	7.5	13	10	8	160	95	22	1.5
B14484	MF-1613-10	10	16	13	10	190	110	28	2.8
B14485	MF-2016-10	17	20	16	13	240	140	34	5.2
B14486	MF-2220-10	25	22	20	16	250	150	40	7.3



Master Link with Sublinks, MT

Designed for use with chain or wire rope. For 3- and 4-leg slings.

Art. no.	Code	WLL tonnes*	L1	L	E	D	l	e	d	Weight kgs
Z100902	MT-6-10	3.5	270	150	90	19	120	70	14	1.8
Z100903	MT-8-10	5.2	300	160	95	22	140	80	17	3
Z100904	MT-10-10	11.5	360	200	120	30	160	95	22	6.4
Z100905	MT-13-10	17	450	250	150	40	200	120	30	14.2
Z100906	MT-16-10	28	500	300	200	50	200	120	32	23
Z101074	MT-20-10	35	550	300	200	55	250	150	40	31.5
Z101281	MT-22-10	53	610	350	200	60	260	140	45	46
Z101282	MT-26-10	70	730	450	250	70	280	160	50	71
Z101283	MT-32-10	91	750	450	260	80	280	160	55	91

