

⚠ WARNING

DO NOT EXCEED WORKING LOAD LIMIT.
USE ONLY G80 & G100 COMPATIBLE COMPONENTS FOR OVERHEAD LIFTING.

Safe Lifters

Pundol Apartments, Shop No. 5 & 6, 160 M.G. Road,
Pune - 411001, (India) Tel +91 20 66013783 / 84 / 85 / 86
Fax +91 20 26350832 Email : safelifters@eth.net

Load Binding Chains

Binder chain assemblies are suitable for truckers, contractors, oil field and highway crews. Grab hook at each end for load binding, hauling, towing and similar applications. Available in Grade 30, 70 and 80, and a variety of sizes and lengths.




THIS TYPE OF CHAIN IS NOT TO BE USED FOR OVERHEAD LIFTING

CHAIN SIZE (INCHES)	STANDARD LENGTHS (FT.)	WORKING LOAD LIMITS (LBS.)		
		GRADE 30	GRADE 70	GRADE 80
1/4	20	1,040	3,150	3,500
5/16	20	1,650	4,700	4,500
3/8	20	3,340	6,600	7,300
1/2	20	4,180	11,300	13,000
5/8	20	6,750	15,800	20,300

Clevis Grab Hooks

• For use with Grade 30 chains only

Size	WLL (lbs)	Dimensions (inches)				Weight (lbs)
		A	B	C	D	
1/4	2,600	0.35	0.38	0.39	1.97	0.45
5/16	3,900	0.41	0.43	0.44	2.27	0.74
3/8	5,400	0.47	0.47	0.51	2.63	1.14
7/16	7,200	0.67	0.55	0.58	2.79	1.45
1/2	9,200	0.73	0.62	0.69	3.13	2.30



• For use with Grade 70 and 80 chains only

Size	WLL (lbs)	Dimensions (inches)				Weight (lbs)
		A	B	C	D	
1/4	3,150	0.36	0.38	0.39	1.97	0.46
5/16	4,700	0.38	0.44	0.43	2.28	0.75
3/8	6,600	0.47	0.47	0.50	2.61	1.10
7/16	8,800	0.67	0.55	0.58	2.79	1.53
1/2	11,300	0.76	0.62	0.67	3.13	2.34

